

MACROBIN® 26 SERIES

The **MacroBin 26 Series**, Macro Plastics' most popular line of bulk harvest and storage bins has a square footprint and is available in three options.



26-R

The MacroBin 26-R is identical to the 26-A-FV, but features narrow vents (3/16" wide).



26-A-S

The MacroBin 26-A-S features solid wall construction that works for pickling, brining, or other liquid applications.



26-A-FV

The MacroBin 26-A-FV is produced with the latest high-pressure injection molding technology, so it's durable, lightweight, and easy to handle.

Feature Highlights

- **Impact-grade copolymer** lasts longer, standing up to heavy day-to-day use, season after season. The molded plastic resists splintering, reducing damage to product and maintenance costs. Bin repair is inexpensive with hot air welding.
- **Lightweight construction** reduces shipping costs and makes MacroBins easier to move; their interlocking foot design makes them safer to stack — up to 10 high.*
- **FDA-approved materials** are certified safe for use with food products, eliminating many HACCP problems associated with wood bins.
- **Ventilation slots** in the 26-A-FV and 26-R facilitate the use of thermofogging, reduce heat absorption and cooling costs, and provide for quicker drying and degreening.
- **Nonporous surfaces** won't absorb water or dehydrate your product like wood bins, and they provide a constant tare weight throughout their use.
- **Rounded corners and smooth surfaces** mean fewer scuffs, abrasions and cuts on your product. Risk of contamination is reduced because there are fewer places for unwanted particles to hide.
- **Easy-to-sanitize** MacroBins keep cleaning costs to a minimum. A high-pressure wash removes most debris; a nonabrasive brush can dislodge any remaining items.
- **Smart MacroBins** utilize securely-attached RFID tags to deliver improved tracking and traceability options.

** See reverse for maximum stack weight specifications.*



Macro Plastics
INCORPORATED

Benefits of Using MacroBins



Increased productivity.
Lightweight MacroBins are easy to handle, move and transport; unique interlocking foot design makes them easy to align and stack.



Reduced cooling costs.
Hundreds of vents in sides and base promote air flow and help your products cool down quicker.




Reduced bin repair costs.
MacroBins are virtually maintenance free; repairs are easy with hot air welding.



Better sanitation and reduced contamination.
Smooth, nonporous surfaces are easy to sanitize and won't trap debris, breed bacteria, or absorb chemicals like wood bins.



Improved pack outs.
Rounded corners and smooth surfaces mean fewer scuffs, abrasions and cuts on your product.



Improved traceability and bin security.
Several identification methods including RFID tags and attractive foil embossing are available.

Specifications for the MacroBin 26-A-FV

Load Capacity:	1,300 pounds
Volume Capacity:	49,603 cubic inches (+/- 4%)
Tare Weight:	87.5 pounds
Maximum Stack Weight ¹ :	12,000 pounds (long term, ambient temperature) 13,000 pounds (short term (<1 month), ambient temperature) 15,000 pounds (long term, cold storage (35° F and below))
Molding Process:	High-pressure injection molding
Material:	Copolymer Polypropylene, U.V. stabilized
Approval:	FDA-regulated material
Container Design:	Double wall corner and center posts
Foot Design:	Two full-length feet with positive interlocking feature
Ventilation Slots:	1 3/4" (L) x 5/16" (W) in sides 1 1/4" (L) x 5/16" (W) in base Over 600 air vents in sides and base for uniform air flow; rounded surfaces on interior edges of slots
Fork Lift Entry:	Two-way: 3" opening with patented integral slide-entry
Handholds:	Two
Label Holders:	Two
External Dimensions:	47 3/4" (L) x 47 3/4" (W) x 28 1/2" (H)
Internal Dimensions:	44 1/2" (L) x 44 3/8" (W) x 24" (H)
OPTIONS:	<ul style="list-style-type: none"> ■ MacroLid ■ Customer identification with RFID tags or foil embossing

Specifications for the MacroBin 26-R

Similar to 26-A-FV except:

Tare Weight:	89.5 pounds
Ventilation Slots:	Narrow: 1 3/4" (L) x 3/16" (W) in sides 1 1/4" (L) x 3/16" (W) in base Rounded surfaces on interior edges of slots

Specifications for the MacroBin 26-A-S

Similar to 26-A-FV except:

Volume Capacity:	49,603 cubic inches (+/- 4%) / 215 gallons
Tare Weight:	92 pounds
Ventilation Slots:	None

Notes: Dimensions assume tolerance of 1/8". Volume capacities assume tolerance of 5% and tare weights assume a tolerance of 4% unless noted otherwise. Ambient temperature approximately equal to 75° F. Data is subject to change.

¹ Stack Weight = (weight of bin contents + tare weight of bin) X number of bins in stack

* Please refer to maximum stack weight specifications listed above.



Macro Plastics
INCORPORATED

CORPORATE HEADQUARTERS:

2250 Huntington Drive
Fairfield, CA 94533
phone 800/845-6555
fax 707/437-1201
e-mail: info@macroplastics.com
www.macroplastics.com