


MACROBIN® DOUBLESHTUTTLE

The **MacroBin DoubleShuttle** is an ultra-large, vented bulk plastic bin with folding sidewalls and a detachable pallet. It has an industry standard footprint, a large bin capacity of 70,000 cubic inches, and hundreds of ventilation slots, making it the perfect choice for storing fresh produce in bulk – up to 1,300 pounds.



Fully collapsed, up to 220 empty DoubleShuttle bins can be loaded on a 53' trailer.



DoubleShuttle

Easy to set-up and knock-down, the MacroBin DoubleShuttle is ideal for closed-loop distribution systems.

Feature Highlights


- **Four-point latch system** facilitates easy set-up and knock-down. Folded sidewalls store upright, five wall sets on one pallet, creating an efficient five-pack module for shipping and storage.
- **Hundreds of ventilation slots** help your products cool down quicker, reduce heat absorption and minimize cooling costs. They also provide for quicker drying and degreening.
- **Lightweight design** (only 126.5 pounds) makes handling easy and reduces shipping costs. High-impact resistance and unique structural integrity stand up to heavy day-to-day use, season after season.
- **FDA-approved materials** are certified safe for use with food products, eliminating many HACCP problems associated with wood bins.
- **Nonporous surfaces** won't absorb water or dehydrate your product like wood bins, and they provide for a constant tare weight throughout their use.
- **Interlocking foot design and high load bearing support columns** make the DoubleShuttle easier and safer to stack — up to 5 high.*
- **Easy-to-sanitize, smooth surfaces** are splinter resistant and keep your cleaning costs to a minimum. A high-pressure wash removes most debris; a non-abrasive brush can dislodge any remaining items.
- **Smart MacroBins** utilize securely-attached RFID tags to deliver improved tracking and traceability options.

* See reverse for load capacity and maximum stack weight specifications.



Macro Plastics
INCORPORATED

Benefits of Using MacroBins



Increased productivity
Ideal for closed-loop distribution systems, the four-point latch system facilitates fast and easy set-up and break-down.



Greater storage capacity.
Store five-pack of folded sidewalls in one pallet for optimum storage capacity.



Faster and safer stacking.
Positive interlocking foot design allows for secure stacking up to 5 bins high.*



Reduced cooling costs.
Hundreds of ventilation slots promote airflow and help products cool faster.



Better sanitation and reduced contamination.
Smooth, nonporous surfaces are easy to sanitize and won't trap debris, breed bacteria, or absorb chemicals like wood bins.



Improved traceability and bin security.
Several identification methods including RFID tags and attractive foil embossing are available.

Specifications for the MacroBin DoubleShuttle

Load Capacity:	1,000 pounds (long term, ambient temperature) 1,300 pounds (long term, cold storage 35°F and below)
Volume Capacity:	70,000 cubic inches
Tare Weight:	126.5 pounds (+/-5%)
Maximum Stack Weight ¹ :	4,000 pounds (long term, ambient temperature) 7,000 pounds (long term, cold storage 35°F and below)
Molding Process:	High-pressure injection molding
Material:	Copolymer Polypropylene, U.V. stabilized
Approval:	FDA-regulated material
Container Design:	Load bearing corner support columns with durable, folding walls and detachable pallet base
Foot Design:	Positive interlocking feet
Ventilation Slots:	2" (L) x 5/16" (W) in sides 1 9/16" (L) x 5/16" (W) in base Hundreds of air vents in side panels and floor to facilitate air flow; rounded surfaces on interior edges of slots
Fork Lift Entry:	Four-way; long side 2" opening, short side 3 9/16" opening
Label Holders:	Four
External Dimensions:	40 1/6" (L) x 47 7/8" (W) x 47" (H)
Internal Dimensions:	36 1/2" (L) x 44 1/2" (W) x 42" (H)
OPTIONS:	■ Customer identification with RFID tags or foil embossing

Notes: Dimensions assume tolerance of 1/8". Volume capacities assume tolerance of 5% and tare weights assume a tolerance of 4% unless noted otherwise. Ambient temperature approximately equal to 75° F. Data is subject to change.

¹ Stack Weight = (weight of bin contents + tare weight of bin) X number of bins in stack

* Please refer to maximum stack weight specifications listed above.



Macro Plastics
INCORPORATED

CORPORATE HEADQUARTERS:

2250 Huntington Drive
Fairfield, CA 94533
phone 800/845-6555
fax 707/437-1201
e-mail: info@macroplastics.com
www.macroplastics.com